



On Q Selective Call intercomm system



- Extend The Reach Of Any "made For iPod" Component, Or Any 30 Pin iPod Enabled Home Theater System, To An iPod From 3 Feet To 330 Feet
- Balanced/differential Audio To Preserve Audio Quality And Reject Noise And Hum Pickup. Also Prevents Mutual Cross-talk Between The Audio, Video, And RS232
- Balanced/differential Video To Preserve Video Quality And Reject Noise And Hum Pickup. Also Prevents Mutual Cross-talk Between The Audio, Video, And RS232
- Includes Power Supply
- connect as many as 3 door units

#### Technical Details

- On-Q part # F7596-AB
- talk to visitors at your door
- connects to inQUIRE intercom system with CAT-5 cable
- installs in a 2-gang weatherproof electrical box (like a heavy die-cast aluminum)
- system expansion allows you to



#### Technical Details

- On-Q part # IC1400-WH
- includes three intercom room units, one intercom main console, one intercom module, one door chime, and a 12V power supply
- room units, console, and intercom module connect with CAT-5 cable
- system expandable to 12 room units and 2 door units

- warranty: 1 year

#### Ipod Wall Dock - Iport



afar with integrated IR and two-way control. It's as easy and stylish as iPod. Free yourself from the constraints of wires and share your music and photos. 70003 IW-3 Adds Factory Pre-Loaded Balanced Audio Module/Substitution of a Balanced Audio Wallplate. Rated for placement up to 500 feet away from the amp or receiver.

#### IW-3 In-Wall Dock Bal Audio

iPort—The first In-Wall Music System for iPod

iPort connects your iPod to any stereo or entertainment center. Control it from

## Escent Music Controller and Management

Marantz 5 disk Changer – plays all formats



### Technical Details

- Plays DVD-V, DVD-A, SACD-Multi, SACD-Stereo, DVD-R/RW, DVD+R/RW, SVCD, VCD, CD, CD-R/CD-RW, MP3, WMA, JPEG, DiVX
- HDMI Output with Scaling (1080p, 1080i, 720p and 480p)
- 192kHz/24-Bit Audio DAC
- 216MHz/12-Bit Video DAC
- Progressive Scan w/3:2 Pull-Down

### Product Details

- Product Dimensions: 16.8 x 17.3 x 3.1 inches ; 22 pounds
- Shipping Weight: 22 pounds ([View shipping rates and policies](#))
- ASIN: B000MGMHW6
- Item model number: VC6001

Marantz 4023 2 channel receiver



#### Technical Details

- 2 Channel x 80 Watts
- Pre-Out/Main-In Terminals Speaker A & B
- 4 Video Inputs / Subwoofer Output
- IR Flasher Input, Triple IR Code Sets
- Front Panel "Lock Out"

Marantz SR4003 Home Theater Receiver



80 W - 7 Channels - 7 Channels, 7.1 Speakers, 4.1 Speakers - 80 W - Remote Control  
GUARANTEED IN STOCK BRAND NEW FREE SHIPPING Specifications New  
Cosmetics, based on the Reference Series 80 Watts x 7 Channels All Discrete Amplifier  
Stages HDMI v1.3a Switching/ v1.1 Repeating: 3-In/1-Out Multi-channel

#### Technical Details

- 80 Watts x 7 Channels All Discrete Amplifier Stages
- HDMI v1.3a Switching/ v1.1 Repeating: 3-In/1-Out
- Multi-channel (7.1) LPCM via HDMI capability
- M.R.A.C. Auto Calibration
- 3 Assignable Component Inputs

#### Product Details

- Product Dimensions: 36 pounds
- Shipping Weight: 36 pounds ([View shipping rates and policies](#))
- ASIN: B001EU0HLM
- Item model number: SR4003
- Average Customer Review: No customer reviews yet. Be the first.

- Date first available at Amazon.com: August 25, 2008

Would you like to [update product info](#) or [give feedback on images](#)?

## Product Description

### Product Description

Marantz SR4003 Home Theater Receiver with 80W X 7 Discrete Power Amplifier Want a full-featured surroundsound receiver? One that brings you as close to the A/V experience as possible while still leaving your "rainy day" bank balance untouched? A quick look at the Marantz SR4003 may convince you that might be all you need. With power, flexibility, and advanced features, it brings you all the performance you expect from Marantz. And that's quite a step above the ordinary, isn't it? Features: \*New cosmetics/chassis \* HDMI 1.3 Repeating: 3-In/1-Out \* Dolby TrueHD, DTS HD Master Audio \* Transcoding to HDMI \* Scaling to 1080P \* Dual Component Outputs \* Sirius & XM-Ready with Discrete IR Commands Specifications: FM TUNER SECTION: Frequency Range 87.5 - 108.0 MHz Usable Sensitivity IHF 1.8  $\mu$ V/16.4 dBf Signal to Noise Ratio: Mono/Stereo 75/70 dB Distortion: Mono/Stereo 0.2/0.3 % Stereo Separation: 1 kHz 45 dB Alternate Channel Selectivity: 400 kHz 60 dB Image Rejection: 98 MHz 70 dB Tuner Output Level: 1 kHz - 75 kHz Dev 800 mV AM TUNER SECTION: Frequency Range: 520 - 1710 kHz Signal to Noise Ratio: 50 dB Usable Sensitivity: Loop 400 $\mu$ V/m Distortion: 400Hz, 30 % Mod. 0.5 % Selectivity: 20 kHz 70 dB AUDIO SECTION: Power Output (20 Hz ? 20 kHz/THD=0.08%) Front L&R: 8 ohms 80 W / Ch Center: 8 ohms 80 W / Ch Surround L&R: 8ohms 80 W / Ch Surround Back L&R: 8 ohms 80 W /Ch Front L&R: 6 ohms 105 W / Ch Center: 6 ohms 105 W / Ch Surround L&R: 6 ohms 105 W / Ch Surround Back L&R: 6 ohms 105 W / Ch Input Sensitivity/Impedance: 180 mV/ 47 Kohms Signal to Noise Ratio(Analog Input / Pure Direct) 105 dB Frequency Response (Analog Input / Pure Direct): 8 Hz -100 kHz ( $\pm$  3 dB) (Digital Input / 96 kHz PCM) 8 Hz - 45 kHz (3 dB) VIDEO: Television Format: NTSC Input Level/Impedance: 1 Vp-p/75 ohms Output Level/Impedance: 1 Vp-p/75



Power your multi-room audio system with the Marantz ZS5300. This versatile six-channel amplifier lets you extend high-quality audio from your main entertainment area to other rooms in your home. You can enjoy warm stereo sound in three different rooms, or connect up to three ZS5300s together to power speakers in as many as nine separate areas simultaneously. The latest digital amplifier technology ensures plenty of clean power and reliable, cool-running operation.

Other key features include individual volume control adjustments that let you fine tune listening levels for each zone in your multi-room system. The ZS5300's "Party Mode" allows you to route any one of the three connected audio sources to all zones at the same time to flood your home with beautiful music at your next get together.

### [Read More](#)

#### Details:

- 6-channel multi-zone amplifier
- 60 watts RMS per channel into 6 ohms (40-20,000 Hz) at 0.05% THD
- signal to noise ratio: 85 dB
- frequency response: 10-30,000 Hz (-1 dB)
- 3 stereo RCA audio inputs, one for each zone
- 3 independent turn-on circuits for multi-zone applications
- independent level controls for each zone
- infrared remote control
- weight: 18.7 pounds
- 17-5/16"W x 4-5/8"H x 14-1/2"D
- warranty: 3 years

#### Max 5100-PM Power Management



With the additional feature of Power Sequencing the M5100-PM guards against blown fuses and potentially damaging speaker thump by automatically powering outlets on

and off in sequence. The M5100-PM also features Clean Power Level 3 also improves picture and sound quality with 60% more efficiency than Clean Power Level 2.

#### Key-Digital 8 to 8 VIDEO MATRIX SWITCHER

- Professional Video Matrix Switcher
- Composite, Component, S-Video, RGBHV
- 500MHz Bandwidth
- LED Indicators
- Multiple Control Options



The KD-MSV8X8 Fat Boy Series Video Matrix Switcher & Distribution Amplifier (1 Unit(s)) from Key Digital is a professional audio matrix switcher that features (8) inputs and (8) outputs. Each one of the (8) outputs can be seamlessly connected to any one of the available (8) inputs. Inputs and outputs can also be managed as zones of input or output signals. This model consists of (1) unit. It is a scalable solution and advanced matrix switching configurations are made possible by daisy chaining multiple units together to scale capacity.

Direct support for component video and composite is included by default with this model. It will also switch S-video by using an optional adapter cable. RGBHV mode is additionally possible by using (2) input and output sections for each RGBHV source.

It offers a bandwidth capacity of 500MHz and supports resolutions up to 1080p. Front-panel LEDs provide a visual indicator of source selection and input-output status.

This unit may be controlled via a front-panel pushbutton control set, an IR remote control, or an RS-232 control. It is compatible with most industry-standard control

systems that use RS-232, including AMX (supports AMX DDDP Dynamic Device Discovery Protocol), Cresttron, Control4, RTI, Universal, and Xantech, among others.

## Key Features

- Video Matrix Switcher

Use this professional video matrix switcher to route any of (8) inputs to any of (8) outputs, individually or in zones.

- Formats

This unit supports analog component and composite video by default, but may also be configured to manage S-video and RGBHV as well.

- Scalable

Advanced matrix switching configurations are made possible with this model by daisy chaining multiple units together to increase capacity.

- Bandwidth

This unit offers a bandwidth capacity of 500MHz.

- LEDs

LED lights provide a visually indicator of line status.

- Controls

It can be controlled via a front-panel pushbutton control set, an IR remote control, or an RS-232 control port.

## Volume Control – Zone 3



#### 4 Device Connecting Block for K3/K4



Provides power connections for up to four (4) RTI in-wall system controllers. Also combines and routes the infrared outputs from the in-wall system controllers to a single output for connection to an RTI control processor. Dual power sense inputs are provided for sharing status feedback to all of the touchpanels. A 4.3Amp, 16VDC power supply is included. 5" H x 9.4" W x 1.0" D.

#### RKM-1 Multi-zone Audio Keypad - Gray



The RKM-1 is a simple, intuitive keypad designed for flush-mount installations in walls or cabinets. Designed for multi-room audio control, the RKM-1's open architecture provides the flexibility to control almost any multi-zone receiver or distributed audio system. Sized for a single gang electrical box, the RKM-1 incorporates eight fully-programmable hard buttons and a customizable LED film which provides feedback of power status, selected source, and volume level

#### 8 Device System Controller



The T1 has eight source and four general purpose buttons with interchangeable keycaps plus 38 assignable/programmable keypad buttons. The T1 Universal System Controller is programmed using the intuitive TheaterTouch™ Designer Software. Includes a Lithium-Ion Battery and a docking station. A non-volatile Flash memory stores system configuration even when power is not present. When used with optional accessory devices, the T1 is capable of infrared and radio frequency transmission, power sensing for reliable operation, and RS-232 communications. It has the same features and specs as the T2+ except run time (continuous) of 20 hours minimum, run time (average use) of 10 to 30 days, 9.25" length and weighs 7.0 oz. with battery.

### 3.5" Color Handheld System Controller



The T3 is RTI's ultimate handheld universal controller. With a full color TFT LCD display, powerful 32-bit MCU, and 32MB of memory, the T3 takes remote control to a new level. The amazing T3 Universal System Controller combines the power and flexibility of a graphic LCD touchscreen with an ergonomic design that permits effortless one-handed operation. Combined with the other TheaterTouch™ products, the T3 becomes a robust commercial-quality control system. The T3 maintains the perfect balance between a large touchscreen and frequently used hard buttons. It is thinner, lighter, and has better ergonomics for one-handed operation than any product in its class. The T3 takes complete control of the home theater, replacing all other remotes. It features a bright, high-contrast TFT LCD that can display custom buttons, text, graphics, and animations. In addition to the backlit display, there are 16 hard buttons that allow easy access to frequently used functions. Programming is easy and convenient thanks to the Windows® based TheaterTouch Designer software. The T3 is more than just a universal remote control—it's an expandable control system. When used with RTI accessory devices, the T3 is capable of RF transmission through walls and cabinets, power sensing for reliable operation, and RS-232 communications for advanced control.

Niles HD5R (Pr)

(FG00882) Includes Speakers, Frames, Grilles and Brackets



High BL magnet structure with vented pole piece

- 1 inch Teteron tri-laminate tweeter housed in a precision adjustment mechanism
- Custom perforated speaker baskets protect woofer from construction debris
- Molded ABS baffle with anti-resonant wave bracing
- BumpBack(TM) magnet for increased throw
- Front-mounted bass and treble controls
- Moisture-resistant construction
- IR sensor knockout
- Snap-in baffle assembly
- Two-piece, no strip speaker terminal
- Depth behind wall: 3-5/8 inch deep (assumes 1/2 inch drywall)

Frame/Grille

- 100% aluminum grilles will not rust
- Color-matched frame/grille
- Microperf grill hides speaker components from view
- Frame mates with bracket to securely clamp sheetrock

Bracket

- Includes Quicksnap new construction wings
- Scored wings for flexible placement between studs
- Extra thin wings minimize sheetrock bulge

- Four wire ties prevent losing wires in walls

Niles Audio CM730DSFX 7" Surround Effects Loudspeaker with Pivoting Woofer NEW!



- Patented Woofer Assembly Fully Pivots Up To 20° To Focus The Bass And Midrange Tones Directly Into The Listening Area
- Twist And Lock Baffle And Frame Mechanism Facilitates Quick Installation And Trouble-free Upgrades
- Integrated Woofer/baffle Design Delivers Greater Low Frequency Response By Employing A 7" Woofer
- Polypropylene Cone Is Light, Strong And Well Damped To Provide Best In Class Bass Response
- Butyl Rubber Surround Damps Resonance And Provides Exceptional Durability
- Dual 1 Pivoting Fluid-cooled UltraSilk Dome Tweeters Provide Clear And Detailed High Frequency Response
- Bridge-mounted Surround Effects (FX) Tweeter Array Directs The High Frequency Sounds At Opposing Angles To Create Realistic Surround Sound Effects
- Includes Flush-mount MicroPerf Aluminum Grille For A Clean And Unobtrusive Look
- Adjustable Dipole/Bipole And Effects Level Controls Allow Precise Room Matching
- Five-year limited warranty

Niles Audio CM750 In-Ceiling Speakers  
7" Two-Way Ceiling Mount Loudspeaker



- Integrated Woofer/baffle Design Delivers Greater Low Frequency Response By Employing A 7" Woofer Where Competitive Models Of The Same Outer Size Employ 6 1/2" Woofers
- Injection-molded TCC™ (Talc, Carbon, And Ceramic-filled) Cone Is Extremely Rigid To Reduce Breakup, Lower Distortion And Provide Enhanced Bass Response
- Butyl Rubber Surround Damps Resonance And Provides Exceptional Durability
- 1" Fluid-cooled Teteron® Dome Tweeter Offers Ultra-wide Dispersion And Silky-smooth High-frequency Response
- Proprietary Bridge-mounted Tweeter-adjustment Mechanism Focuses The High Frequency Sound In Any Direction Up To 20° Without Diffraction
- Includes Flush-mount MicroPerf™ Aluminum Grille For A Clean And Unobtrusive Look
- Weather Resistant Construction Reduces Installation Limitations And Provides Unique Solutions In Moist Environments Or Outdoors Under Eaves

Niles Audio SW-12 Subwoofer  
12" 260 Watt Subwoofer



- Advanced Amplifier Design Provides Significant Dynamic Power
- 12" Injection-molded TCC (Talc, Carbon And Ceramic-filled) Polypropylene Woofer With Butyl Rubber Surround
- RCA LFE Input Bypasses All Filtered Inputs
- Left And Right Line-level Inputs Include Fixed 80Hz High-pass Filter
- Cascade Audio Outputs Facilitate Easy Connection Of Additional System Components And Speakers
- On/off System Trigger Input Accepts 3V-30V AC/DC
- Cascade Trigger Output Allows Easy Expansion To Other Triggered System Equipment
- Gold Plated Connection Terminals Ensure Long Term Performance
- Subwoofer Phase Control Switch Ensures Optimal System Integration
- Adjustable Low Pass Filter 60Hz 125Hz
- Adjustable Woofer Level Control

## LST-CTR In-Wall Center Channel Speaker, White (Single)



### Technical Details

- Single 2-way in-wall center channel speaker with recommended power handling of 10 to 150 watts
  - Dual 5.25-inch mica-filled polypropylene woofers with butyl rubber surrounds for tight, pleasing mids and lows
  - 1-inch liquid-cooled ElastoDynamic tweeter produces crisp highs; 45 Hz to 21 kHz frequency response
  - Terminals accept up to 12-gauge speaker wire; front-mounted Treble Cut, Bass Cut, and Dialogue Enhance switches
  - Magnetically shielded; mounting cutout measures 13.25 x 7.12 inches (W x L) and 3.12 inches deep; 5-year warranty
- › [See more technical details](#)

### Product Details

- Product Dimensions: 12.5 x 3.5 x 6.2 inches
- Shipping Weight: 11 pounds ([View shipping rates and policies](#))
- Shipping: Currently, item can be shipped only within the U.S.
- ASIN: B000BL338E
- Item model number: LSTCTR

### Samsung PN58A550 - 58" High Definition 1080p Plasma TV



This SAMSUNG 58" widescreen plasma HDTV with 1080p resolution is big enough to transform any space into the ultimate home theater. Advanced features like a FilterBright™ to protect against glare and 1,000,000:1 dynamic contrast ratio for stunningly realistic images, will simply amaze you and your guests. Take your home entertainment experience to the next level with the SAMSUNG PN58A550 plasma HDTV.

- Widescreen aspect ratio High-definition 1920 x 1080 pixel resolution: presents video and text with outstanding clarity and resolution.
- 1,000,000:1 dynamic contrast ratio:  
Two of the most important factors in overall picture quality, contrast and brightness, achieve new heights in these latest generation plasma panels. Together with the DNIe proprietary circuitry, Samsung's new plasma TV's give the most stunning realistic picture quality ever from a flat panel set.
- 100,000 hour panel life:  
Samsung's new panels are made to last longer, so you can be confident that the

high picture quality will endure.

- Ultra FilterBright anti-glare technology
- Built-in digital tuner: (ATSC/NTSC/Clear-QAM)  
High-Definition Built-in tuner analog and digital tuners receives and decodes digital/analog standard-definition and HDTV signals from over-the-air broadcasts (antenna required)
- DNIe The Samsung Digital Natural Image engine:  
This exclusive Samsung technology dramatically improves the picture by enhancing the contrast, detail, white balance and reduces noise.
- Anti Burn-in Technology:  
Auto pixel shift (user programmable), Signal pattern processing function, All White
- Bottom speakers:  
Direct down-firing speakers, 10-watts per channel built-in audio amplifier to drive the integrated stereo speakers.
- SRS TruSurround XT:  
TruSurround is a patented SRS technology that solves the problem of playing 5.1 multichannel content over two speakers. TruSurround delivers a compelling, virtual surround sound experience through the two speaker internal playback system.
- Natural true color:  
Samsung Plasma TV can display Natural True Color with 18 bit processing. And new algorithm adjusting color balance will let you enjoy the 'As-is color'
- ACE Silhouette editor:  
(false contour reduction) delivers clear images without contour lines.
- Entertainment Mode:  
Entertainment Mode allows customized picture settings, optimized for different content (e.g., sports, movies, gaming) control.
- V-Chip system:  
This allows blocking of rated TV and movie programs determined by the parent to contain objectionable content.
- Trilingual on-screen display:  
Displays options in English, Spanish or French.

- Power saving (off/high/middle/low)
- Side A/V ports:  
Provides easy connections so you can connect a camcorder, digital camera, or any other digital device with no hassles.
- Removable swivel stand:  
If you want to install your TV on your wall, you can easily remove the stand and use a compatible wall mount to safely and stylishly attach your TV to the wall. See our recommended accessories or TV essentials bundled packages.
- Auto wall mount compatible:  
3-dimensional operation via TV's remote control; no external IR receiver required.
- Inputs & Outputs:  
3 HDMI High Definition Multimedia Interface, 2 Component video inputs, Side & rear A/V inputs, PC input, 2 RF antenna inputs, Wiselink (USB 2.0), Headphone jack, RS-232.
- HMDI-CEC:  
HMDI-CEC feature lets you control all your CEC-enabled peripherals using just one remote.
- Dimensions & Weight:  
TV w/o stand: 55.4" (W) x 33.9" (H) x 3.9" (D) / 126.3 lbs.  
TV with stand: 55.4" (W) x 36.5" (H) x 13.6" (D) / 137.8 lbs.
- Manufacturer Warranty  
One year parts and labor for residential, in-home service





Samsung LN32A450 - 32" high-definition LCD TV



Enjoy a theater-like experience in your own home with the 32" LN32A450. A remarkable 10,000:1 dynamic contrast ratio delivers an extraordinary picture comprised of vivid colors and outstanding quality. Want to feel the action, not just see it? A 6 ms response time promises smooth sailing and virtually no blurring when you're watching movies and sports events while SRS TruSurround XT delivers a virtual surround sound experience.

CCFL - Cold Cathode Fluorescent Lamp

Enjoy brighter, more true-to-life pictures and vivid colors that will simply amaze you. SAMSUNG LCD HDTVs give you 92% coverage of the National Television System

Committee's standard as compared to the 72% that competitors offer. That translates to brilliant images that truly enhance your entertainment experience.

6 ms response time

One of the most important features for an LCD panel is the pixel response time. Response time refers to how long it takes pixels to turn from completely white to black and back again—the lower the milliseconds (ms), the faster the response time is. A fast 6 ms response time virtually eliminates any blurring and gives you smooth-motion action scenes.

SAMSUNG's DNle - Digital Natural Image engine

SAMSUNG's exclusive Digital Natural Image engine makes the sharpest and clearest images possible, regardless of the signal you're receiving. Five image processors and a six-time density enhancer ensure the best picture from any source with the truest colors and highest contrast.

10,000:1 contrast ratio

Contrast and brightness levels achieve new heights in this LCD TV. Get a more realistic, sharper picture quality that's sure to catch your eye.

Hidden Bottom Speakers

Less is more. Just because you can't see the stylishly concealed speakers doesn't mean you won't hear the unbelievably clear sound radiating from them.

HDMI-CEC

Control all of your High Definition Multimedia Interface connected devices with one-touch control in a single universal remote.

### Specifications

#### Video

- Screen Size: 32"
- Resolution: 1366 x 768
- Dynamic Contrast Ratio: 10,000:1
- Viewing Angle: 178 degrees / 178 degrees
- Response Time: 6 ms
- DNle (Digital Natural Image Engine): DNle +

## Audio

- Sound Effect System: SRS TrusurroundXT
- Sound Output(RMS): 10W x 2

## Input & Output (Side)

- HDMI: 1
- composite (AV): 1
- S-Video: 1
- Headphone: Yes

## Input & Output (Back)

- HDMI: 2
- Composite (AV): 1
- S-Video: No
- PC input (D-sub): 1
- Component(Y/Pb/Pr): 2

## Dimension

- Set size(WXHXD) with stand: 31.4" x 22.7" x 9.9"
- Set size(WXHXD) without stand: 31.4" x 20.7" x 3.7"
- Package size(WXHXD): 35.7" x 24.2" x 8.2"

## Weight

- Set weight with stand: 27.9 lb
- Set weight without stand: 24 lb
- Package weight: 36.1 lb

## Power consumption

- Operation power consumption: 180W
- Stand-By power consumption: < 1W

More Product Information for the Samsung LN32A450 - 32" high-definition LCD TV

---

## Specifications

### General Information

Manufacturer	Samsung
Manufacturer Part Number	LN26A450
Manufacturer Website Address	www.samsungusa.com
Product Model	LN26A450
Product Name	LN26A450 26" LCD TV
Product Type	LCD TV

#### Technical Information

Actual Screen Size	26"
Compatible Technology	HDTV
Aspect Ratio	16:9
Response Time	8 ms

#### Video

Video System	ATSC
Maximum Resolution	1366 x 768
Contrast Ratio	5000:1

#### Audio

Number of Speakers	2
Total Output Power	5W
Audio Decoding	Stereo
Sound System	Surround

#### Interfaces/Ports

Ports	3 x HDMI Digital Audio/Video In
Ports	2 x Component Video In
Ports	S-Video In
Ports	2 x A/V In
Ports	15-pin HD-15 VGA In
Ports	Headphone
Ports	RF Antenna In



#### Westinghouse Digital Electronics UNDER-CABINET Mount Silver

Always wanted a TV or computer in your kitchen but don't have the counter space? This ingenious bracket flips the display down for viewing and then tucks your LCD display conveniently under the cabinet for storage.

## ViewSonic N1630w 16IN LCD TV



16" LCD TV - widescreen - 720p - HDTV - black

Product Description	ViewSonic N1630w - 16" LCD TV
Product Type	LCD TV
Diagonal Size	16" - widescreen
Dimensions (WxDxH)	14.8 in x 2.6 in x 10 in - without stand
Color	Black
Digital Television Certification	HDTV
Resolution	1366 x 768
Display Format	720p
Input Video Formats	480p, 720p, 1080i, 480i
Video Interface	Component, composite, HDMI, S-Video
PC Interface	VGA (HD-15)
HDCP Compatible	Yes
Technology	TFT active matrix
Progressive Scan	Yes
Image Aspect Ratio	16:9
Digital TV Tuner	ATSC, QAM
Analog TV Tuner	NTSC
Sound Output Mode	Stereo
Speaker System	2 speakers
Remote Control	Remote control - infrared

Power  
Manufacturer Warranty

AC 120/230 V ( 50/60 Hz )  
1 year warranty



Niles Audio Niles RS5 Speckled Granite  
Acoustic suspension design, frequency response 70-21,000 Hz, enclosure looks like a  
granite rock, weatherproof design

